

AS/4A NOTES:  
CEILING & BULKHEADS REVERSED WITH  
AS/4A REVISIONS NOT CLOUDED

- CEILING NOTES:**
1. TYPICAL GYPSUM BULKHEAD W/40 ACUSTIC INSULATION
  2. CEILING TYPE C1 NO ACUSTIC INSULATION AT BATHROOMS AND LAUNDRY CLOSES TYP.
  3. KITCHEN BULKHEAD @ 240mm AFF TYP. U.N.O. (@ 220mm AFF ON LEVELS 3 AND 4)
  4. ALL PLUMBING PENETRATING SLAB ABOVE TO BE WRAPPED W/ 38mm ACUSTIC BATT EXCEPT IN BATHROOM CEILING.
  5. PARTITIONS AROUND C1 CEILING TO BE FILLED W/ ACUSTIC BATT ABOVE THE CEILING. EXTEND GYPSUM TO US SLAB ABOVE ON ONE SIDE OF PARTITION MIN.
  6. WHERE PLUMBING FROM ABOVE IS LOCATED OVER A ROOM BELOW OTHER THAN A BATHROOM PROVIDE AN INSULATED C1 CEILING, PLUS WRAP THE PLUMBING IN ACUSTIC BATT.

- PLAN DRAWING LEGEND:**
- DENOTES PAINTED C1A GYPSUM BULKHEAD AT 2200 AFF UNLESS NOTED
  - MTL3 YELLOW METAL PANEL CLADDING
  - WTA EXTERIOR WALL ASSEMBLIES W/40 UNLESS NOTED OTHERWISE

- ♿ DENOTES BARRIER-FREE DESIGNATED RESIDENTIAL SUITE
- ♿ DENOTES ROOF DRAIN AND ROOF DRAINAGE LAYOUT. REFER ALSO TO SLAB EDGE PLANS FOR SLOPES AND SLAB ELEVATIONS

- REFER TO DWG. A200 FOR DETAILS OF WINDOW WASHING SYSTEMS:**
- AP ANCHOR POINT
  - DB DAWT BASE
  - RDB RECESSED DAWT BASE
  - RRR RECESSED ROOF ANCHOR
  - RA ROOF ANCHOR
  - RS ROOF ANCHOR - WALL MOUNTED
  - WWS WINDOW WASHING RIGGING SLEEVE

