

[illegible]

- | | | | |
|---|---|----------------|--------|
| COLUMN AND WALL
SCHEDULE
BELOW GRD. FLOOR |  | PROJECT NO. | 1205 |
| | | OWNER/DESIGNER | H.W. |
| | | DATE REVISION | 1/2003 |

TABLE 2		SHEAR WALL		REINFORCING	
WALL THICKNESS	DIRECTION	WALL EXPOSED OR ENCLOSED BOTH SIDES	WALL EXPOSED ONE SIDE	ENCLOSED SIDE	
150mm	HORIZ.	10 @ 270 (1 LAYER)	10 @ 270 (1 LAYER)		
	VERT.	10 @ 270 (1 LAYER)	10 @ 270 (1 LAYER)		
200mm	HORIZ.	10 @ 400 EA. FACE	10 @ 300	10 @ 450	
	VERT.	10 @ 400 EA. FACE	10 @ 300	10 @ 450	
250mm	HORIZ.	10 @ 350 EA. FACE	10 @ 240	10 @ 450	
	VERT.	10 @ 350 EA. FACE	10 @ 240	10 @ 450	
300mm	HORIZ.	10 @ 270 EA. FACE	10 @ 200	10 @ 400	
	VERT.	10 @ 270 EA. FACE	10 @ 200	10 @ 400	
350mm	HORIZ.	15 @ 450 EA. FACE	15 @ 340	15 @ 450	
	VERT.	15 @ 450 EA. FACE	15 @ 340	15 @ 450	
400mm	HORIZ.	15 @ 400 EA. FACE	15 @ 300	15 @ 450	
	VERT.	15 @ 400 EA. FACE	15 @ 300	15 @ 450	
450mm	HORIZ.	15 @ 350 EA. FACE	15 @ 260	15 @ 450	
	VERT.	15 @ 350 EA. FACE	15 @ 260	15 @ 450	

NOTE: SIZE AND SPACING OF DOWELS TO BE SAME AS VERTICAL REINF. IN WALL

Jablonsky, A.
and Partner
**CONSULTING
ENGINEER**

1000 N. 1ST ST.
DOW MILLS, WIS.
TEL. 416-447 2405
FAX 416-447 2771
E-mail jjablonska@att.net

0002525000
ENCLOSURE
P.F. AST
130015
PROVINCE, CT
06460