



# HUNTER SPOT RI 2xLED 1200 18W 1230 Lm 3000K 40°

Code: 1U3.1122.8332.1

 **intra lighting**  
all visible

L.3



## Photometric Data

### Classification

BZ	-
UTE	-
DIN	-
CIE	-

### Glare Evaluation

X=4H, Y=8H	-
Radiant Class	-
UGR - transverse	-
UGR - longitudinal	-

## Options

1U3.1122.8332.1	HUNTER SPOT RI 2xLED 1200 18W 1230 lm 3000K 40° white 120/277V dimmable 0-10V	3,3
1U3.1122.8332.2	HUNTER SPOT RI 2xLED 1200 18W 1230 lm 3000K 40° black 120/277V dimmable 0-10V	3,3
1U3.1122.8332.5	HUNTER SPOT RI 2xLED 1200 18W 1230 lm 3000K 40° grey 120/277V dimmable 0-10V	3,3

## Description

Professional recessed ceiling trim-less adjustable spot luminaire

Trim: made from aluminium designed for flush installation in false ceilings ragging from 12,5 to 25 mm

Housing: steel sheet housing, white or black colour

Ring: optical units made of die-cast aluminium (same colour as trim); orientation in horizontal and vertical axes  $\pm 35^\circ$  /  $\pm 35^\circ$  thanks to double asymmetrical fixing

LED options:

- LED 1800 23W @ 700mA (1880-1990 lm) ; beam angle 24° or 40°

- LED 2700 34W @ 1050mA (2740-2900 lm) ; beam angle 24° or 40°

LED colour: 3000K or 4000K

LED driver: supplied with dimmable 0-10V constant current driver

Power supply: 120/277V; 50-60Hz

Mounting: all necessary mounting accessories included